



Satisfy Professional's Needs

Screwdriver series

Easy handling and High maneuverability



FS2500



FS2701



FS2700

Best possible tool body for screwdriving.



FS2500

Optimum
for fastening teks
or hex screw.

One touch locator
Easy to install or remove

Ingenious exhaust vents
Exhaust air does not blow dust
and debris around when the
tool is used close to floor level.

**Variable speed
control**
by trigger switch

**Reversing
switch**

More durable belt clip
composed of a sheet metal
sandwiched between plastic layers
for added strength

**Best possible tool body
for screwdriving**
ergonomically designed to;
- minimize hand fatigue and pain
even in long continuous operation.
- give maximum
power thrust.
- allow for much
smoother and
easier trigger pull.



Rubberized soft grip
provides comfortable grip and more
control while minimizing hand fatigue
and pain.

LED job light
convenient for
operation
in dark job sites



Bit holder
Spare bit can be stored.

FS2700

Removal front cap
for changing from self-drilling
screws to hex bolts operation.

6 Stage torque adjustment
for a wide range of applications.

FS2701

Bit sleeve
for easy bit change.

6 Stage torque adjustment
for a wide range of applications.

Accessories

Locator (for Model FS2500)
For Magnetic socket bit



Front cap (for Model FS2700)



For bit size	Part No.
1/4"	450963-4
5/16"	450967-6
3/8"	450968-4

Locator assembly (for Model FS2500)
For Magnetic bit holder + Phillips insert bit



Type	Part No.
Short	122867-7
Long	122868-5

For Phillips bit L=45mm (type NZ)

Size	Part No.
12	322070-2

For Magnetic bit holder + Phillips insert bit
(type MZ)

Size	Part No.
12	322263-1

For Socket bit (type NZ)

Size	Part No.
15.5	322069-7

For Magnetic Socket bit L=50mm (type MZ)

Size	Part No.
-	322120-3

For Magnetic Socket bit L=65mm (type MZ)

Size	Part No.
1/4"	322124-5
5/16"	322125-3
3/8"	322119-8
7/16"	322126-1

Screwdriver

FS2500/ FS2700/ FS2701

419

	FS2500	FS2700	FS2701
Double Insulation			
Variable Speed			
Reversing			
Built-in Job Light			
Torque Setting 6 (FS2700, FS2701)			
Continuous rating Input	570W	570W	570W
Capacity Drywall screw:	5mm (3/16")	6mm (1/4")	6mm (1/4")
Self drilling screw:	6mm (1/4")	6mm (1/4")	6mm (1/4")
Hex. screw:	-	6mm (1/4")	6mm (1/4")
Driving shank (Hex.)	6.35 mm (1/4")	6.35mm (1/4")	6.35mm (1/4")
No load speed (rpm)	0-2,500	0-2,500	0-2,500
Dimensions** (L x W x H)	280 x 70 x 207mm (11" x 2-3/4" x 8-1/8")	301 x 70 x 207mm (11-7/8" x 2-3/4" x 8-1/8")	283 x 70 x 207mm (11-1/8" x 2-3/4" x 8-1/8")
Net weight*	1.5kg (3.4lbs)	1.8kg (4.0lbs)	1.7kg (3.8lbs)
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)

Standard Equipment Magnetic Socket Bit (FS2500 only)

**for countries providing noise suppressor
*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z15235-2 AJ-BA