



Satisfy Professional's Needs

Hammer Drill HP1630 / HP1631 16 mm (5/8")



Photo : HP1631

HIGH PERFORMANCE

with Cylinder-shaped motor housing and aluminum gear housing cover

HIGH POWER 710W MOTOR



Photo: HP1631

Hammer Drill

Double Insulation

Variable Speed

Reversing

Keyless Chuck (HP1631 only)



HP1631/ HP1630 16mm (5/8")

85

Continuous rating Input Capacity

HP1630

HP1631

710W
Concrete : 16mm (5/8")
Steel : 13mm (1/2")
Wood : 30mm (1-3/16")

Concrete : 16mm (5/8")
Steel : 13mm (1/2")
Wood : 30mm (1-3/16")

Impacts per minute (ipm)

HP1630

HP1631

0-48,000

0-48,000

No load speed (rpm)

HP1630

HP1631

0-3,200

0-3,200

Dimensions

HP1630

HP1631

(L x W x H)

(L x W x H)

(L x W x H)

Net weight

HP1630

HP1631

1.9kg (4.2lbs)

1.9kg (4.2lbs)

1.9kg (4.2lbs)

Power supply cord

HP1630

HP1631

2.0m (6.6ft)

2.0m (6.6ft)

Standard Equipment Side grip, Chuck key (HP1630 only)

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23404-2 AI-AI