Satisfy Professional's Needs



Jig Saw JV0600



Get Satisfaction Powerful. Durable. Maneuverable.





Toolless blade clamp

Blade can be attached with single action - simply by pushing it into the clamp; can be also removed easily with single action.



Change lever for 3 orbital settings and straight cutting Optimum cutting action can be selected simply by turning the Lever.



Compact housing design for clear view of cutting area.

Jig Saw

Double insulation

Variable Speed

Orbital Cutting



Compact and lightweight design

ð

Tnakita.

has been achieved while maintaining both strong power and high maneuverability.

> Best possible ergonomic handle Provides comfortable grip and more control while minimizing hand fatigue and pain. Ribbed rubber grip enables all finger tips to hold the handle securely.

Covered with non-slip elastomer



Variable speed control by dial



Connectable to Vacuum cleaner using optional Hose

Aluminum support housing Increases the rigidity of the portion for fixing Base plate.

Rigid Aluminum Base bevels 0 to 45 degrees left and right.

Blow-off device

added to protect the rod portion from saw dust for enhanced performance against dust.

JV0600

Continuous rating Input Capacity Length of stroke Strokes per minute (spm) Dimensions(L x W x H) Net weight Power supply cord

650W Wood: 90mm (3-1/2") Steel: 10mm (3/8") 23mm (7/8") 500 - 3,100 236 x 77 x 199mm (9-1/4" x 3" x 7-7/8") 2.4kg (5.2lbs) 2.5m (8.2ft)

Standard Equipment Jig Saw Blade, Hex Wrench

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

23mm (7/8")



Stroke length



Bayonet Shank Jig Saw Blade

Dust Collecting

Carrying Case