

Expand your working capacity Trackita





LED job light switch

Anti-restart function

(for countries where regulations require it) prevents accidental startup for safety even if the machine is plugged to power source with the switch on.

Easy-to-Read Scale

with large graduations and magnifying lens.



Wheeled stand for easier mobility

Stand with two caster wheels and a lifting handle adds mobility for convenient repositioning of the





LED job light

6 LEDs illuminate working surface for easier cutting in dark places.



Bevel cutting

base can be tilted up to 45-degrees.



Easy connecting with vacuum cleaner

Both 63mm and 100mm hoses can be connected.

soft wood




High / Low speed selection for excellent results in both hard and



Accessories

Band saw blade Thickness: 0.5 mm



Width	No. of teeth per inch	Application	Part No.	
16mm	4	Wood/ for cross-cut	B-16667	
13mm	4	Wood/ for universal	B-16673	
6mm	6	Wood/ for curve-cut	B-16689	
16mm	14	Nonferrous metal	B-16695	

Extension table set

Dust box

keeps the work place clean.

Part No. JM21000300



Circular cutting attachment set

Part No. JM21000320



Belt sanding attachment set

Part No. JM21000330



Band Saw



Mechanical 2-speed



Built-in job light



Dust collecting

LB1200F

Power supply cord

Continuous rating Input

Thickness of cut: 165mm (6-1/2") Throat: 305mm (12") Capacity

Hi: (50Hz) 800m (60Hz) 1,000m/min. Lo: (50Hz) 400m (60Hz) 500m/min. Blade speed 615 x 775 x 1,600mm (24-1/4" x 30-1/2" x 63") Dimensions(L x W x H)

Net weight 81.2kg (179.0lbs)

2.5m (8.2ft)

Standard Equipment Band Saw Blades, Rip Fence, Angle Rule, Push Stick 2, Nozzle 93, Band Saw Stand, Hex Wrenches

Items of standard equipment and specifications may vary by country or area. *weight according to EPTA-Procedure 01/2003

Makita Corporation